

GLOBAL POWER SOLUTIONS

DELIVERING POWER, DELIVERING CONFIDENCE

TOWNSVILLE - BRISBANE - PERTH

13KVA **GP15000SE3**

12.5kVA Prime / 13kVA Standby

Comprehensive Specification Sheet
Electrical and Mechanical Data



hi-EARNS

3ph

GP1500SE3

12.5kVA Prime / 13kVA Standby / Three Phase

FEATURES & BENEFITS

- 13VA standby power at 415 @ 50Hz 3000rpm
- High-quality and reliable Single Cylinder 762cc Hiearns diesel engine
- Ideal for home and business applications
- Silent canopy which can stand outside with lockable doors
- Automatic changeover (ATS), maintenance free batteries and trickle charger OPTIONAL
- 2 wire and 5 wire auto starts built in
- H-specification insulation, brushless alternator with AVR provides stable output
- High-temperature and oil pressure sensor to protect against engine damage
- Easy to use digital controller with auto/manual start options
- All sets undergo a comprehensive testing/pre-delivery inspection prior to delivery
- Peace of mind of earlier of 12 Month/500 hour warranty



CANOPY

- Ventilation parts are designed with modular principles
- Weather resistant and lined with sound reducing foam
- Galvanised steel canopy - painted with powder paint
- Panel window
- Lockable doors on each side
- Easy maintenance and operation
- Easy lifting and moving
- Thermally insulated engine exhaust system
- Exterior emergency stop push button
- Sound attenuated

CHASSIS

- The complete generator set on wheels
- Steel chassis and anti-vibration pads for engine and alternator
- The generator can be lifted or carefully pushed/pulled by the base frame

CONTROL SYSTEM

Control supervision and protection panel is mounted on the genset base frame. The control panel is equipped as follows:

METERING VIA LCD DISPLAY

- Mains volts (L-L/L-N)
- Generator amps (L1, L2, L3)
- Generator frequency; generator (cos)
- Engine hours run; plant battery (volts)

Overview

Standby power	13 kVA - 10.4KW
Prime power	12.5kVA - 10KW
Phase	Three
Dry weight	225kg
Length	1025mm
Width	650mm
Height	810mm
Fuel tank capacity	30L

AUTOMATIC SHUTDOWN AND FAULT CONDITIONS

- Low oil pressure; charge

GP1500SE3

12.5kVA Prime / 13kVA Standby / Three Phase

TECHNICAL SPECIFICATIONS

*All ratings are quoted at maximum ratings at sea level and derating will be applicable for altitude and power factor.

Engine

Engine make	HiEarns
Engine model	HR1150F
Displacement	762CC
Cylinder bore/Stroke	105mm x 88mm
Fuel system	Mechanical
Governor	Mechanical
Cylinders	1 Cylinder – Air Cooled
Engine output power (3000rpm)	11kW
Turbocharged/normally aspirated	Natural
Cycle	Single Cylinder – 4 stroke
Combustion system	Injection
Compression ratio	-
Fuel tank capacity	30l
Fuel consumption 100%	2.5/h *
Fuel consumption 75%	2.1 l/h *
Fuel consumption 50%	2 l/h *
Fuel consumption 25%	1.7 l/h *
Oil type	15W40
Engine oil capacity	1.9l
Cooling method	Air
Coolant capacity	N/A
Starter	12v DC starter charge rectifier
Engine speed	3000rpm
Filters	Replaceable fuel filter/oil filter/dry element air filter
Battery	Maintenance-free battery including rack and cables
Silencer	Exhaust silencer

Alternator

Alternator	Dingol
Standby power output	13VA
Prime power output	12.5kVA
Insulation class	Class-H with circuit breaker protection
Type	Brush
Phase and connection	3 phase
AVR	Included
AVR model	SX460
Voltage regulation	± 1%
Voltage	415/240
Rated frequency	50Hz
Voltage regulate change	≤ ±10% UN
Phase change rate	± 1%
Power factor	0.8φ
Protection class	IP23 standard/screen protected/drip-proof
Stator	2/3 pitch
Rotor	Single bearing
Excitation	Self-exciting
Regulation	Self-regulating

General

Structure type	Silent weather resistant enclosure
Dimensions Length x Width x Height	1025mm x 650mm x 810mm
Dry weight	225 kg
ATS unit included	Optional
Four-way protection system included	Included